

LPT24



| Model | LPT24SHE | LPT24SHD | LPT24SHL | LPT24SL |
|--|--|--|--|--|
| Image Sensor | 1/3"SONY | | | |
| Horizontal Resolution | ICX673AK CCD,700TV Lines Low Illumination, Effio, WDR, OSD, NR | ICX639BK CCD, 600TV Lines Low Illumination, WDR, OSD | ICX639BK CCD, 540TV Lines Low Illumination | ICX633BK CCD, 420TV Lines Low Illumination |
| Pixels | PAL:795 (H)× 596(V) NTSC :811 (H) × 508 (V) | | | PAL:500(H)× 582 (V) NTSC:510(H)× 492(V) |
| Pan range | 0° ~360° Continue (Not 355°) | | | |
| Tilt range | 0° ~90° Flip | | | |
| Pan Speedt | Max 50° /sec | | | |
| Preset | 16 | | | |
| | RS485 control | | | |
| IR LED | 24pcs, IR working distance:20M | | | |
| Lens | Board Lens 6mm/F2.0 | | | |
| Size | ø 138x142mm | | | |
| Weight | 1000g | | | |
| Model | SDK24 | | | |
| | Special design for LPT24 | | | |
|  | PT Dome controller IR remote controller: Support 99pcs cameras RS-485 communication Baud rate: 2400,4800 and 9600Bps Communication distance: Max.1200m Weight: 350g | | | |